




## HIGH WALL MOUNTED TYPE FAN COIL UNIT

- Digital Display Panel
- Remote Control
- Power-Down Memory Function
- Air-To-Water Heating & Cooling



## Performance

### High wall mounted FCU standard type

Model ( 2 –tube system)			MFP-34BM-C	MFP-51BM-C	MFP-68BM-C	MFP-85BM-C	MFP-102BM-C	MFP-136BM-C		
Power supply			220V,50Hz,1Ph							
Air volume	H	m <sup>3</sup> /h	340	510	680	850	1020	1360		
	M		260	380	515	650	765	1010		
	L		180	260	340	43	520	700		
Static pressure		Pa	0	0	0	0	0	0		
Cooling capacity	TH	H	W	1800	2700	3600	4500	5400	7200	
			BTU/h	6142	9212	12283	15354	18425	24566	
		SH	W	1350	2025	2700	3375	4050	5400	
			BTU/h	4606	6909	9212	11516	13819	18424	
	TH	M	W	1476	2214	2952	3690	4428	5904	
			BTU/h	978	1399	1963	2409	3044	3926	
		SH	L	W	1098	1647	2196	2745	3294	4392
				BTU/h	649	960	1355	1715	2060	2710
Heating capacity	H		W	2700	4050	5400	6750	8100	10800	
	M		W	2146	3219	4293	5366	6439	8586	
	L		W	1512	2268	3024	3780	4536	6048	
Noise	High speed		dB(A)	0.31	0.46	0.62	0.77	0.93	1.24	
Power input	High speed		W	12	14	17	18	22.5	23.5	
Waterflow volume	High speed		m <sup>3</sup> /h	57	67	74	82	55	65	
Pressure dropping			kPa	86	100	110	122	83	97	
Water tube connection(inlet)			ZG1/2"	ZG1/2"	ZG1/2"	ZG1/2"	ZG1/2"	ZG1/2"		
Water tube connection(outlet)			ZG1/2"	ZG1/2"	ZG1/2"	ZG1/2"	ZG1/2"	ZG1/2"		
Coil		Type	Hydrophilic aluminum fin to wear copper tube							
Maximum working pressure			MPa	1.6	1.6	1.6	1.6	1.6	1.6	
Condensing water pipe			mm	ϕ 16	ϕ 16	ϕ 16	ϕ 16	ϕ 16	ϕ 16	
Net dimension	L×W×H		mm	850X300X198	850X300X198	970X315X235	970X315X235	1100X330X235	1100X330X235	
Net weight			kg	11	11	15	15	20	20	

